



# VL300 The Trusted Pin Pad Payment Solution

Effortlessly accept payments with the VL300, a seamless, reliable solution for growing businesses.

#### **User-friendly and Intuitive Experience**

Enjoy a user-friendly experience with a spacious touchscreen display on our intuitive interface. The VL300 offers enhanced visibility in dimly lit environments with backlit keys, providing a user-friendly experience.

#### **Customer Feedback & Satisfaction**

Utilize our integrated built-in customer feedback rating system for insights to refine services and increase customer satisfaction. Elevate your service excellence, one feedback survey at a time.

#### **Enhanced Payment Security**

Provide your customers heightened security features with our enhanced pin pad technology, providing an extra layer of protection during the PIN entry process. The PCI-PTS 6.0 ensures customer security.

#### **Secure and Convenient Contactless Payments**

Embrace the future of payments with advanced EMV technology, ensuring utmost security for transactions. Choose from swipe, tap, and dip card payment options, accompanied by a secure digital signature capture feature, making payments safe and convenient.

### **Features**



Large Scale 3.5" Touchscreen Display



Backlit Keys



EMV



Digital Signature Capture



PCI-PTS 6.0 Certified Pin Pad

## **Specifications**



Processor		32-bit secure microprocessor running a powerful Linux-based operating system
Memory	Flash/RAM	256 MB / 128MB
Display		3.5-inch color TFT LCD featuring a capacitive touchscreen, offering a resolution of 320 $\times$ 480 pixels and supports electronic signature capture
Touchscreen		Yes
Card Reader	Magnetic Stripe	ISO 7810, 7811, 7813 Triple track, bi-directional
	Contact Card	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1
	Contactless	ISO 14443 Type A, B   ISO 18092 NFC Mifare & Sony FeliCa Working Frequency 13.56 MHz
Communication		Ethernet
Audio		Speaker
Keypad	Standard Keys	15
Dimensions (mm)		150(L) x 78.5(W) x 39(H)
Weight		225g
Environment	Operating Temperature	0°C to 50°C
	Storage Temperature	-20°C to 70°C
	Relative Humidity	5% to 90% non-condensing
Certifications		PCI PTS 6.x   EMV L1/L2   payWave   PayPass   ExperssPay   D-PAS   Interac Flash   J-Speedy   FeliCa   UnionPay UICS   TQM





🖂 sales@valorpaytech.com

valorpaytech.com

in □ ⑤ f 🛚



